







Examine all packaging material for small parts that may have come loose during shipment. Periodic checks are recommended to insure that all components are in proper position, tight and free from damage. Keep this assembly instruction for future reference. Adult assembly is required. The product of Hillsdale Furniture, LLC is designed for residential use only. Customer Service Phone Number: 502-562-0000

HARDWARE LIST

- A (10) 1/4" x 5/8" Allen Bolts
- B (4) 1/4" x 3/4" Allen Bolts
- C (6) 1/4" x 1" Allen Bolts
- D (16) 1/4" Flat Washers
- E (16) 1/4" Spring Washers
- F (1) 1/4" Allen Wrench

PIECES LIST

- G (1) Stool Back
- H (1) Seat Base
- I (4) Stool Legs
- J (1) Support Ring
- K (1) Stool Base

PART	QTY	HARDWARE	PART	QTY	HARDWARE
A	10		B	4	
C	6		D	16	
E	16		F	1	

STEP 1

Begin assembly by attaching the Stool Back (G) to the Seat Base (H) with 2 Allen Bolts (C), 2 Spring Washers (E) and 2 Flat Washers (D) from the outside and 2 Allen Bolts (A), 2 Spring Washers (E) and 2 Flat Washers (D) from the inside.

STEP 2

Next attach the Legs (I) to the Stool Base (K) by using 4 Allen Bolts (A), 4 Spring Washers (E) and 4 Flat Washers (D). Do not fully tighten bolts.

STEP 3

Next attach the Support Ring (J) to the inside of the Legs (I) with 1 Allen Bolt (B) per leg. Tighten all bolts from steps 2 & 3 with Allen Wrench (F) provided.

STEP 4

Finally attach the Seat Base (H) to the Stool Base (K) by aligning the holes with those on the swivel metal plate (located on the bottom of the seat base) and securing with 1 Allen Bolt (C), 1 Spring Washer (E) and 1 Flat Washer (D) per hole. Tighten all bolts. The assembly is now complete.

