

TeaRose Loveseat

Assembly Instructions

***WARNING* Heavy! Handle with care! Keep children away from assembly area!**

Tools Required: Adjustable wrench and Slotted Screwdriver (- minus driver)

Parts List:

Back Section	1	Stud Bolts	4
Seat	1	Hex Bolts	8
Arm	2	Lock Washers	16
Flat washer	16	Nuts	16
Legs	4	Slotted Bolts	4

Assembly:

We suggest you assemble the unit on a soft surface to avoid damage to the finish.

Step 1 – Place the seat on a flat level surface, upside down. Attach the 4 legs to the seat using hex bolts with a lock washer and flat washer on each in this order. Hand tighten only at this point.

Step 2 – Stand the assembly upright and thread in the 4 stud bolts in the Back section. Then slip the stud bolts thru the thru hole of the seat section. Secure the back section by slipping a flat washer, a lock washer and a nut on to each of the stud bolts hand tighten only at this point.

Step 3 - Attach the Arms to the Back and Seat section using a Slotted bolt with a lock washer and flat washer in this order on each.

Step 4 – Align the sides with seat and back so the unit is level and the legs are parallel.

Step 5 – Now tighten the bolts to lock the unit in its permanent configuration. ***Caution:** Unit is constructed of cast metal and is brittle. Do not force any part of the assembly and do not over-tighten the fasteners as damage may occur.

After assembly is completed and before first use verify the chair sits level and is stable.

**** Maintenance Recommendation:**

- 1) **Oxidation of cast iron:** The cast iron component of the product is finished with a powder coating process that protects the iron from rusting. However, due to the nature of the iron, rusting is inevitable. It is recommended that the consumer touch up any surface that is scratched or damaged due to wear and tear. Applying an epoxy clear coating is recommended once a year.
- 2) **Aluminum:** The products with aluminum components please be reminded that aluminum is soft metal it is therefore necessary to exercise caution when tightening nuts/bolts/screws on aluminum parts to prevent damaging the treads on the metal.
- 3) **Solid Brass Fasteners:** The fasteners provided are made with solid brass. This item will tarnish after weathering. A brass polish can be use to keep the screws shiny or you can leave it untouched to give it a patina/antique look.

Please do not return product to place of purchase – for customer service issues please call 1-866-656-8666 to speak with customer service between the hours of 9am and 5pm Eastern Standard Time. You may also fax or E-Mail any questions or comments to 1-248-652-1105 / sales@oakland-living.com.

3006-20040909