

# Cabbage Hill Garden Bench and Chair

Assembly Instructions

866-543-4380

---

Tools Needed: Electric or Cordless Drill with Phillips bit. We recommend that you glue the joints with a weather resistant glue, i.e., Tight Bond II is a good one.

The Cabbage Hill Garden Bench consists of 5 different sub-assemblies that need to be assembled together to make a finished bench.

- 1 left side assembly
- 1 right side assembly
- 1 seat assembly
- 1 back assembly
- 1 undercarriage assembly (unassembled)

1. Unpack all parts and identify as one of the above sub-assemblies.
2. The first step is to place the seat assembly into the two side assemblies. Laying either the right or left side (arm and legs) on the floor or a table with the arm down.
3. Screw seat to sides. Secure by using 2 ½ inch screws in pre-drilled holes (2 each side). Using 3 inch screws, attach from outside legs (1 per leg) Repeat for other side.
- 4 You should now have both sides screwed onto the seat and your bench is beginning to take shape. Lay it on its' back (if the back was on) and get ready to put the undercarriage on. First, you must reassemble the 2x4s that make up the rectangular shaped undercarriage. ( See diagram A below and match numbers i.e. 1 to 1 – 2 to 2 etc) Use 2 ½ inch screws to reassemble. Once it is reassembled, slide the undercarriage between the legs and up as far as it will go, with the cut-out longest member to the front. (It should be directly beneath seat) Using 3-inch screws, attach to legs (2 per leg )
- 5, Place back assembly, with screwed side to the back) inside of bench end assembly and attach using 3 -inch screws.
4. Insert plugs into screw holes using a small amount of glue on each one to assure that they will stay in.

## Diagram A:

Top view of under-carriage assembly



Chair has same under carriage.

Top view of under carriage assembly

